## **RECA NORM GmbH**

Am Wasserturm 4 74635 Kupferzell Phone +49 7944 61-300

http://www.recanorm.de



Report of installation

Project:		Supervisor:	
Company:		Assembler:	
Construction stage:		Date:	
Type of anchor	Trade name: (e.g. BZ 10-10/90 A4 or VMU-A 10-10/110 + VMU-SH 16x100 + VMU 345)		
	Number of Approval:		
Batch Number:	Anchor / Stud Cartridge / Glass Capsule		
Base material	Concrete: Masonry: Thickness:	C /	B / mm
Drilled hole	Cutting-ø of drill bit: Depth of hole: certified drill bit: Hammer drilling: Depth stop: Drill hole wet:	yes Ino yes Ino yes Ino yes Ino	mm mm
Cleaning of drilled hole	Method + sequence: Brush-ø: Checked with gauge: Brushed by: Blow-out pump: Compressed air:	yes Tho hand 500ml	_mm  _machine  _750ml bar
Setting depth	Excess length above surface: Interlayer (plaster,screed): Setting depth:		_mm _mm _mm
Fixed part	ø of clearance hole: Thickness:		_mm _mm
Setting tool	Trade name: Length of spike:		mm
Torque wrench	Type: Last calibration: Installation torque:		_Nm
Dimension of the fixing	Edge distance given in drawing or by engineer: kept on site: Spacing between anchors given in drawing or by engineer: kept on site:	yes Ino yes Ino yes Ino yes Ino	
Chemical fixings	Date of expiry: Temperature of cartridge/capsule: Temperature of base material: Chemical Capsule installed with hammer drill: Excess mortar at surface: Time bevor application of installation torque:	□ yes □ho □ yes □ho	

Date:	Signature assembler:	Signature supervisor: